

EXPERIMENTAL ANALYSIS OF ADVANCED COOLING SOLUTIONS FOR CAVITIES OF MULTI-MW CW GYROTRONS

S. Stančulović¹, R. Difonzo², G. Gantenbein¹, S. Illy¹, J. Jelonnek¹, T. Ruess¹, T. Rzesnicki¹, L. Savoldi²

¹Karlsruhe Institute of Technology, Kaiserstr. 12, 76131 Karlsruhe, Germany

²MAHTEP Group, Dipartimento Energia “Galileo Ferraris”, Politecnico di Torino (PoliTo), Torino, Italy

ABSTRACT

The ongoing research and development of high-power fusion gyrotrons demands for an effective cavity cooling system for optimum gyrotron operation [1, 2]. Since the last decade, fundamental experimental research of advanced cooling techniques using mini-channels for high-power gyrotron cavities is carried out at KIT [3]. The test rig consists of the mock-up, 20 temperature sensors, two pressure sensors and the flow meter. The induction heater (6 kW maximal power) induces thermal loads on the cavity inner wall. An acquisition sub-system is implemented in the cavity cooling test system for visualization and recording of the measured values. A test mock-up that contains a cooling system based on 40 mini-channels, with geometry and materials identical to the real cavity of the 170 GHz 2 MW longer-pulse pre-prototype gyrotron, has been designed and integrated into the experimental set-up and systematically tested. The measured results, however, were shadowed by the experimental uncertainties and the comparison to the computed results, which in turn suffered from some uncertainty in the evaluation of the power deposited by the inductive heater, turned out to be difficult [4]. First improvements in the test set-up for the thermal-hydraulic investigation of a cavity cooling are already realized [5]. In order to increase the overall accuracy in the experiments and to eliminate potential uncertainties a set of improvements of the test set-up are implemented: (1) a new flowmeter with improved measurements accuracy, and (2) faster thermocouples, with reaction times < 0.1 s. Additionally a coating of the inner surface of the copper cavity with a Nickel layer of 100 μm thickness was introduced in order to increase the heat load. Further increasing of the induced heat flux in the inner wall of the mock-up will be achieved by increasing the available heating power, i.e. using an induction heater with 4 times higher nominal output power P_{out} , such as MINAC 24/40 ($P_{\text{out}} = 24$ kW). The obtained experimental results provide input to validate numerical models used for the cavity cooling optimization.

Acknowledgements: Part of this work has been carried out within the framework of the EUROfusion consortium, funded by the European Union via the EURATOM research and training programme (grant agreement no. 101052200 - EUROFUSION). Part of the simulations were performed on the EUROfusion High Performance Computer (Marconi-Fusion). Views and opinions expressed are however those of the authors only and do not necessarily reflect those of the European Union or the European Commission. Neither the European Union nor the European Commission can be held responsible for them.

References

- [1] M. THUMM, “Recent advances in the worldwide fusion gyrotron development,” *IEEE Trans. Plasma Sci.*, vol. 42, no. 3, pp. 590–599, 2014, doi: 10.1109/TPS.2013.2284026.
- [2] K. A. AVRAMIDIS, *et al.*, “Numerical Studies on the Influence of Cavity Thermal Expansion on the Performance of a High-Power Gyrotron,” *IEEE Transactions on Electron Devices*, vol. 65, no. 6, pp. 2308-2315, 2018, doi: 10.1109/TED.2017.2782365.
- [3] P. C. KALARIA *et al.*, “Design studies of mini-channel cavity cooling for a 170 GHz, 2 MW coaxial-cavity *Conference (IVEC 2019)*, 28 April - 1 May 2019, Busan, SouthKorea. <https://doi.org/10.1109/IVEC.2019.8745135>
- [4] S. STANČULOVIC, *et al.*, “Calibration of the KIT Test Setup for the Cooling Tests of a Gyrotron Cavity Full-size Mock-up Equipped with Mini-Channels”, *Fusion Engineering and Design*, vol. 172, November 2021, available online, doi: 10.1016/j.fusengdes.2021.112744.
- [5] S. STANČULOVIĆ, *et al.*, “KIT Experimental Setup for Examination of Enhanced Cavity Cooling Technologies for MW CW Gyrotrons in Fusion ECRH Applications”, presented at the 1st German Workshop on ECRH and Gyrotrons, 10 - 12 April 2024, Beilngries, Germany