

Low- and very low- frequency short-circuit current interruption with vacuum

D. Gentsch, E. D. Taylor, A. Lawall, S. Gortschakow

ABSTRACT

The main application for vacuum interrupters (VI) is in electrical power systems at frequencies of $f_r = 50/60 \text{ Hz}$. Other applications at different f_r include rail electrical power systems that run at $16 - 2/3 \text{ Hz}$ and 25 Hz . VI worked successfully in these applications for many years. Green energy applications such as wind turbines, pumped storage, DC to AC converters in solar parks and shipboard applications can generate temporary fault conditions with very low frequencies. Low frequency applications generate very long arcing times and high transferred charge, making current interruption at the current zero (CZ) difficult. This work calculates the interruption performance boundary to frequencies between $0.5 - 2 \text{ Hz}$ based on the test performed at $16 - 2/3 \text{ Hz}$ and 50 Hz . The contact erosion rates were also grouped into three different situations as a function of the current, and the erosion during multiple short-circuit operations from $10 - 40 \text{ kA rms}$ at 50 Hz and at several hundred of amperes at $0.5 - 5 \text{ Hz}$. Test sequences from the generator circuit breaker standard are also examined, such as delayed CZ and very high direct current (DC) offset tests. These tests are effectively equivalent to lower frequency tests. Finally, experiments were performed at 2.4 Hz at $1250 - 1500 \text{ A rms}$ to observe the impact of multiple switching operations on the contacts, metal vapor deposit on the ceramics, and heat build-up in VI. Three different contact systems and sizes were tested.

References

- [1] High-Voltage Switchgear and Controlgear—Part 100: Alternating-Current Circuit-Breakers, IEC Standard 62271-100, ed. 3.0, 2021.
- [2] P. G. Slade, The Vacuum Interrupter: Theory, Design, and Application. New York, NY, USA: CRC Press, 2021.
- [3] M.B. Schulman, P.G. Slade, L.D. Loud, Wangpei Li, “Influence of Contact Geometry and Current on Effective Erosion of Cu-Cr, Ag-WC and Ag-Cr Vacuum Contact Materials,” IEEE Trans. Comp. Packag. Technol., vol. 22, no. 3, pg. 405, Sept. 1999. Errata: IEEE Trans. Comp. Packag. Technol., vol. 23, no. 1, pg. 194, Mar. 2000.
- [4] D. Gentsch, S. Goettlich, M. Wember, A. Lawall, N. Anger, E. D. Taylor, “Interruption performance at frequency 50 or 60Hz for generator breaker equipped with vacuum interrupters,” Proc. 26th ISDEIV Int. Symp. Discharges Electr. Insul. Vac., 2014, pg. 429.
- [5] D. Gentsch, A. Lawall, E. D. Taylor, “Interruption performance of vacuum circuit breaker under low- and very low frequency condition,” Proc. 30th ISDEIV Int. Symp. Discharges Electr. Insul. Vac., 2023, pp. 406.
- [6] E. Philippow, Taschenbuch Elektrotechnik, Band 5, VEB Verlag Technik Berlin, 1980.
- [7] High-voltage switchgear and controlgear – Part 101: Synthetic testing, IEC Standard 62271-101, ed. 3.0, 2021.
- [8] A. Bianco, B. Brewer, M. Stefanka, M. Riva, “High performance smart MV apparatus for arc furnace applications,” Proc. 25th Int. Conf. Electricity Distribution CIGRE, 2019, paper 0883.
- [9] M. Schlaug, L. Dalmazio, U. Ernst, X. Godechot, “Electrical Life of Vacuum Interrupters,” Proc. 22nd ISDEIV Int. Symp. Discharges Electr. Insul. Vac., 2006
- [10] High-Voltage Switchgear and Controlgear—Part 1: Common Specifications for Alternating Current Switchgear and Controlgear, IEC Standard 62271-1, ed. 2.1, 2021.
- [11] P. G. Slade, R. K. Smith, “A comparison of the short circuit interruption performance using transverse magnetic field contacts and axial magnetic field contacts in low frequency circuits with long arcing times,” Proc. 21st ISDEIV Int. Symp. Discharges Electr. Insul. Vac., 2004, pp. 337.
- [12] Railway applications for alternating current switchgear Part 1: Circuit-breakers with nominal voltage above 1kV, EN 50152-1: 2007.
- [13] I. Gramberg, M. Kurrat and D. Gentsch, “Electron probe micro analysis and surface resistance measurement investigation of copper chrome coatings on vacuum circuit breaker ceramic surfaces following switching operations,” Proc. 25th ISDEIV Int. Symp. Discharges Electr. Insul. Vac., 2012, pg. 99