

STUDIES ON HIGH-POWER MILLIMETER-BAND TRAVELING WAVE TUBE AMPLIFIERS WITH MULTIPLE SHEET ELECTRON BEAMS

N.M. Ryskin^{1,2}, R.A. Torgashov^{1,2}, A.E. Ploskih,² G.V. Torgashov¹, V.N. Titov², A.G. Rozhnev^{1,2}

¹Saratov Branch, V.A. Kotelnikov Institute of Radioengineering and Electronics RAS,
38 Zelenaya st., Saratov, Russia, 410019

²Saratov State University, 83 Astrakhanskaya st., Saratov, Russia, 410012

E-mail of corresponding author: ryskinm@gmail.com

ABSTRACT

Many applications, such as advanced telecommunication and radar systems, spectroscopy, biomedical research etc. require high-power, compact sources of sub-THz (0.1-0.3 THz) radiation. To improve output performance of vacuum-tube sub-THz amplifiers and oscillators, using of high-aspect-ratio sheet electron beam is very promising [1]. Multiple sheet beam offers an opportunity of further increase of the power level. Several multiple-sheet-beam traveling-wave tubes (TWTs) have been proposed [2]-[5]. In this paper, the results of design and development of two TWTs of such a kind are presented.

The first one is the TWT with multiple-tunnel meander-line slow-wave structure (SWS) and vertically arranged sheet beams [4]. The V-band SWS is designed and simulated. The TWT is driven by a 200-mA, 18-kV double sheet beam. Over 250 W average output power and 25-30-dB small-signal gain can be attained with 1-2 W input power at 68 GHz. The second one is the G-band TWT with a horizontally arranged multiple sheet beam interacting with a higher-order transverse mode of a staggered dual-grating SWS. An electron gun with three elliptic sheet beams is designed, simulated, and fabricated. Beam transportation in a solenoidal magnetic field is simulated and experimentally studied. The results of 3-D PIC modeling of beam-wave interaction are presented showing nearly 100-W output power and over 25-dB gain. Technology for microfabrication of the multiple-tunnel SWS is discussed.

This work is supported by Russian Science Foundation under Grant No. 17-12-01160

References

- [1] Y.M. SHIN, A. BAIG, L.R. BARNETT, N.C. LUHMANN, J. PASOUR, and P. LARSEN, IEEE Trans. Electron Devices 58 (2011) 3213.
- [2] A. GEE and Y.-M. SHIN, Phys. Plasmas 20 (2013) 073106.
- [3] G. SHU, G. LIU, L. CHEN, H. BAMBARANDAGE, and ZH. QIAN, J. Phys. D: Appl. Phys. 51, (2018) 055107.
- [4] G.V. TORGASHOV, R.A. TORGASHOV, V.N. TITOV, A.G. ROZHNEV, and N.M. RYSKIN, IEEE Electron Device Lett. 40 (2019) 1980.
- [5] ZH. LU, K. DING, R. WEN et al., IEEE Electron Device Lett. 41 (2020) 284.