

# HEMP

Innovative Electric  
Propulsion Technology for  
Commercial and  
Scientific Spacecraft




9th VDE ITG International Vacuum  
Electronics Workshop 2024


[www.thalesgroup.com](http://www.thalesgroup.com)



# Outline

- > Fundamentals of propulsion and electric propulsion
- > Principal of operation – HEMP
- > Performance of the HEMP Thruster Module EV0
- > Roadmap and Outlook: HEMP Thruster Module EV0+






# Fundamentals of Propulsion: Moving in Space - Velocity demand – $\Delta v$ – orbit transfer

> To move from one orbit to another orbit, the object has to gain velocity ( $\Delta v$ )

	$\Delta v$	$v$
Launch to		0 m/s
LEO		7.802 m/s
Transfer to	+4.098 m/s	
GEO		11.900 m/s
Operation: 15a NSSK	+750-825 m/s	

Typical values  
figures may vary depending on launch site, trajectories, orbits



## Fundamentals of Propulsion: Moving in space – Example: North-South Station Keeping

### > NSSK-North South Station Keeping


> Gravitational forces push Geostationary satellites out of their Equatorial orbit finally into ecliptic plane

### > To compensate:

- ▶ Thrust maneuvers 2x per day
- ▶ Around the orbital nodes



$$\Delta v = v_e \ln \left( \frac{m_0}{m_f} \right)$$



## Fundamentals of Propulsion: Rocket equation – thrust through reaction


> The rocket equation describes acceleration of vehicles by expelling parts of its mass with constant high speed

$\Delta v$  change of velocity of the vehicle  
 $v_e$  effective exhaust velocity  
 $m_0$  start mass (wet mass)  
 $m_f$  final total mass (dry mass)

$\Delta v$  increases with exhaust velocity and with relative amount of propellant ejected

Imperative:

➔ High exhaust velocity required to keep wet mass as low as possible (higher payloads possible)




# Fundamentals of Propulsion: Chemical vs. Ion Propulsion

## > Chemical: Energy stored in Propellant

- specific energy limited
- mass acceleration through thermal expansion
- high thrust due to high propellant mass flow:  $T = \dot{m}_p v_e$
- exhaust velocity limited by temperature at nozzle inlet:  
 $v_e \propto \sqrt{T_1}$

## > Ion Propulsion: Energy not in propellant, provided from outside

- specific energy unlimited
- mass acceleration by electrical field
- typically low thrust
- exhaust velocity defined by supplied electrical power:  
 $v_e \propto \sqrt{U}$



## Principal of operation – Thales High Efficiency Multistage Plasma Thruster HEMPT

### > thruster with permanent magnets and a cylindrical dielectric discharge channel

- ▶ Minimized plasma-wall contact:
  - magnetic cells form strong confinement of electrons in cusp-mirror configuration → almost no channel erosion
- ▶ High ionization efficiency:
  - due to efficient electron confinement
- ▶ Efficient ion acceleration by electric field
- ▶ Long life time and performance stability:
  - due to negligible channel erosion
- ▶ Thruster and system architecture with minimum complexity: cost-efficient & reliable
- ▶ Concept allows wide operational range (voltage and current)


# Principal of operation – Hollow Cathode Neutralizer HCN

## > HCN Operational Principle:

- ▶ Low voltage high density Xenon/Krypton discharge serves as conductor for emitter electrons to form neutralizing plasma bridge
- ▶ Advantage: High current and current density possible
- ▶ Example: 3A of electron current is conducted through 1mm<sup>2</sup> !

## > Properties:



- ▶ Ba impregnated Metal Matrix W/Os electron emitter
  - high thermionic emission at moderate temperatures (low work function material)
  - low ignition and sustaining voltage for keeper discharge and for plasma bridge
- ▶ Cathode technology with best flight heritage from TWTs
  - minimized technological risk, high reliability and life time



# Principal of operation – HEMPT Confinement

## > HEMPT Operational Principle:



- ▶ Electrons are efficiently trapped in a cusp-mirror configuration (magnetic cells)
- ▶ Plasma electrons are prevented from contacting the discharge channel walls



# Performance of the HEMP Thruster Module (HTM) EV0 – Plume Characteristics

> Separated ionization and acceleration zones cause most of the ions to be generated at anode potential

→ high ion acceleration efficiency





# Recent Success: Thales Thruster HEMPT 3050

Fully qualified thruster

TRL 8  
Life Test

Heinrich Hertz satellite:  
Launch: 5<sup>th</sup> July 2023  
In orbit since 21<sup>st</sup> July 2023




## KEY TECHNICAL ELEMENTS

Thrust: 44 mN  
ISP: 2400 s  
Power: 1.4 kW  
Operating Voltage: 1000V  
Total Impulse: 1.47 MNs  
Life time >9000 h operation  
qualified for space




## Performance of the HEMP Thruster Module EV0

- > 200 W – 700 W flexible power rating
- > Thrust: up to 32 mN
- > Operating Voltage 300 V – 800 V
- > Propellant: Xenon or Krypton
- > ISP: up to 2100 s ( $ISP = \frac{v_e}{g}$ , with  $g = 9,81 \text{ m/s}^2$ )
- > Total Impulse target: >1.0 MNs
- > 1.5kg mass (depending on harness length)
- > Dimensions: approx. 180x190x90 mm



## Performance of the HTM EV0 – Krypton Endurance Test with Engineering Model

- > 4650 firing hours, 600V-700W working point, ~360 kNs
- > Test interrupted due to time schedule, thruster module still operational
- > Thrust degradation ~ 2%, specific impulse degradation ~ 4%



HTM-EV0 Engineering Model

# Performance of the HTM EV0 – Different Propellants and OPs




	300 W	500 W	600 W	700 W
300 V	Thrust 15.3 mN ISP 1100 s	Thrust 24.1 mN ISP 1250 s	Thrust 28.2 mN ISP 1295 s	Thrust 32.0 mN ISP 1330 s
400 V	Thrust 14.5 mN ISP 1230 s	Thrust 22.8 mN ISP 1400 s	Thrust 26.3 mN ISP 1450 s	Thrust 29.9 mN ISP 1500 s
600 V	Thrust 12.8 mN ISP 1390 s	Thrust 20.1 mN ISP 1615 s	Thrust 23.6 mN ISP 1700 s	Thrust 27.0 mN ISP 1760 s
800 V	Thrust 11.3 mN ISP 1455 s	Thrust 17.9 mN ISP 1780 s	Thrust 21.2 mN ISP 1880 s	Thrust 24.7 mN ISP 1955 s




	300 W	500 W	600 W	700 W
300 V	Thrust 12.6 mN ISP 1125 s	Thrust 20.5 mN ISP 1305 s	Thrust 23.4 mN ISP 1295 s	Thrust 28.2 mN ISP 1425 s
400 V	Thrust 12.0 mN ISP 1305 s	Thrust 19.1 mN ISP 1495 s	Thrust 22.3 mN ISP 1585 s	Thrust 25.8 mN ISP 1660 s
600 V	Thrust 10.9 mN ISP 1445 s	Thrust 17.6 mN ISP 1755 s	--	Thrust 23.6 mN ISP 1940 s
800 V	Thrust 9.3 mN ISP 1585 s	Thrust 15.1 mN ISP 1910 s	--	Thrust 20.5 mN ISP 2140 s

### HTM EV0 Performance - Xenon



### HTM EV0 Performance - Krypton




# Roadmap and Outlook: HEMP Thruster Module EV0+

TRL 8

Final qualification

Delta design

BB tested



**HEMPT 3050**

**HEMPT EVO**

**HEMPT EVO +**

**HEMPT EV1**

Technology demonstrator

Low cost small engine for constellations

Low cost medium engine for any orbits

Low cost medium engine for any orbits

1400 W  
Thrust : 44 mN  
ISP : 2400 s

200 – 700 W  
10 – 32 mN  
Up to 2200 s

500 – 1200 W  
30 – 45 mN  
Up to 2800 s

1000 – 3000 W  
30 – 140 mN  
Up to 3200 s


Xenon  
**In orbit**

Xenon & Krypton  
**Qualified / in production**

Xenon & Krypton  
**Ready to start dev.**

Xenon & Krypton  
**BB tested – In standy**

# Roadmap and Outlook: HEMPT recent commercial successes




DLR


Thales thruster onboard Heinrich Hertz mission (Ariane 5 Launch on July 5th 2023)




multiple



commercial



projects



# Conclusion

## > Fundamentals of propulsion and electric propulsion

- ▶ High exhaust velocity beneficial

## > Principal of operation – HEMP




- ▶ Simple design with high exhaust velocity and no channel erosion

## > Performance of the HEMP Thruster Module EV0

- ▶ High ion acceleration efficiency at different operating points with different propellants

## > Roadmap and Outlook: HEMP Thruster Module EV0+

- ▶ Commercial success HTM EV0 and HTM EV0+ ready for development





**Thank you**

[www.thalesgroup.com](http://www.thalesgroup.com)



# Contact

---

**Gabriel SUSKE**

Electric Propulsion System Engineer

 +49 731 40729 314

 [Gabriel.suske@thalesgroup.com](mailto:Gabriel.suske@thalesgroup.com)