

INNOVATIVE MINICHANNEL COOLING SYSTEM FOR GYROTRON CAVITIES

Alberto Leggieri¹, Ferran Albajar², Stefano Alberti³, Kostantinos A. Avramidis⁴, Rosa Difonzo⁵, Lukas Feuerstein⁶, Eleonora Gajetti⁵, Gerd Gantenbein⁶, Jérémy Genoud³, Jean-Philippe Hogge³, Stefan Illy⁶, John Jelonnek⁶, George Latsas⁴, François Legrand¹, Christophe Lievin¹, Rodolphe Marchesin¹, Tomasz Rzesnicki⁶, Ioannis Tigelis⁴, Francisco Sanchez², Laura Savoldi⁵, Sebastian Stanculovic⁶, Athanasios Zekas⁴ and Manfred Thumm⁶

¹Microwave & Imaging Sub-Systems, THALES Vélizy-Villacoublay, France; ²Fusion for Energy, Barcelona, Spain,

³Swiss Plasma Center, EPFL, Lausanne, Switzerland; ⁴Dept of Physics, National and Kapodistrian University of Athens, Greece,

⁵Dipartimento di Energia "Galileo Ferraris", Politecnico di Torino, Italy, ⁶IHM, Karlsruhe Institute of Technology, Germany

Technical needs: Increasing performances are constantly demanded to new gyrotrons. The heat load on the cavity wall is a major limiting factor. In Raschig Rings (RR) cavities, heat transfer is limited by the minimum Glidcop cavity thickness that ensures mechanical stability. Actual mini-channel (MC) designs on the TH1507U 1.5MW 140GHz CW gyrotron have shown unacceptable stresses (440MPa in nominal conditions). The proposed system increases the heat exchange while limiting thermo-mechanical stresses and anisotropic deformations.




Figure 1. TH1507 RR structure and stress profile (nominal conditions).




Figure 2. First develop. of TH1507 MC structure and stress profile (nominal).

Solution and design: The structure relies on an adaptive profile of the outer element (jacket) that dilates and displaces during operation.

- To increase heat exchange: The fluid flow is placed as close as possible to the heated wall.
- To limit stress: A bypass gap closes the MC once the thermal steady state is reached
- To avoid friction: The axial displacement of the (flexible) water jacket equals the cavity thermal expansion to follow cavity motion.
- To ensure the radial correct position of the jacket: Multiple inlets injects a radial flow that counterbalances the MC inner pressure.

Patent pending n° 2110917 France - 14 October 2021.




Figure 3. Functional diagram of the proposed cooling system.

Computed performance: Compared to Raschig rings cooling solution, for the same initial peak heat load of 1.85 kW/cm² and water flow of 50 l/min, a multiphysics simulation TH1507U cavity, shows a max temperature reduced from 279° C to 228° C with a stress level of 211 MPa, giving margin of 38 MPa before plasticization. The fatigue life is of 537000 ON/OFF cycles (reaching steady state regime).




Figure 4. Temperature, velocity and fatigue life plots.

	Peak heat load (kW/cm ²)	Peak cavity temperature (°C)	Max V.M. Stress (MPa)	Yield strength (MPa)	Stress margin before Plasticization margin (MPa)	Pressure drop @ 50 l/min (bar)
TH1507U RR	1.96	279	292	220	-72	0.9
TH1507U MC	2.27	228	211	248	38	1.9

Table 1. Maximum values and comparison with RR solution (@50 l/min).




Figure 5. Profiles of heat load (left) and temperature distribution (right).




Figure 6. Profiles of radial displacement (left) and Von Mises Stress (right).

Mockup realization: The proposed device can be realized by traditional mechanical processes and proven brazing techniques. A mock-up has been manufactured for technological validation at KIT. Pressure drop have been measured and thermodynamic tests are ongoing at KIT.




Figure 7. Glidcop cavity and Mockup. **Figure 8.** Thales Hydrodynamic test bench. **Figure 9.** Pressure drop (meas vs sim). **Figure 10.** KIT Induction test stand.

Acknowledgments: This work is supported by EUROfusion, Euratom (Programmes 2014–2018 and 2019–2020 Grant No.633053 and 2021–2025 Grant No.101052200) and F4E (contract F4E-OPE-992). The views expressed herein do not necessarily reflect those of F4E, IO, EUROfusion or EU Commission.