


Simulation of Gyrotron Multistage Depressed Collectors using Beam-Shape Transform and $E \times B$ Drift

C. Wu, I. Gr. Pagonakis, S. Illy, G. Gantenbein, M. Thumm, and J. Jelonnek

Institute for Pulsed Power and Microwave Technology



This project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement number 633053. The views and opinions expressed herein do not necessarily reflect those of the European Commission.

Outline

- Motivation
- Overview of Concepts
- New Idea: the $E \times B$ MDC
 - Electric and Magnetic Fields
 - Electron Beam Trajectory Simulation
 - Discussion of Secondary Electrons
- Conclusion

Motivation of MDCs for Gyrotrons

- Sort spent electrons and apply different decelerations to each category.
 - Reduce power consumption.
 - Save operation cost.
 - Reduce thermal loading and cooling / pumping requirement.
 - Increase life-time (due to reduced stress and fatigue effects).

- Comparable to the sorting of balls, However, with more challenges.

- State-of-the-art for CW gyrotrons
 $\eta_{\text{total}} \approx 50 \%$ ($\eta_{\text{collector}} = 50 - 60 \%$)

- **Goal:** $\eta_{\text{total}} > 60 \%$,
i.e. $\eta_{\text{collector}} > 74 \%$.



Quality sorting of table tennis balls. *source: youtube*

Concepts of MDCs for Gyrotrons

both \vec{A} and φ are
rotationally
symmetric

- Trajectories overlap each other, referred to Busch's theorem
- Can be modelled by the effective potential


at least one of the
potentials is
asymmetric

- Trajectories fully separable using the $E \times B$ drift
- Can be easily analyzed

Challenges for the Symmetric Concept 1

Strong stray field from the super-conducting gyrotron magnet

- $B > 0.1$ T at the entrance of a collector.
- Still > 10 mT on 1 m axial offset to the entrance.


- Effective magnetic potential: $\varphi_m = \frac{1}{2m} \left(\frac{P_\theta - qr A_\theta}{r} \right)^2$  φ_m of the stray magnetic field in the collector

- “Tennis Ball” model:
Electrons are **confined** in the narrow potential valley.

- **Solution:** compensate and reduce the stray field.




Challenges for the Symmetric Concept 2



- 73.3 % η_{col}
 $\cong 60.17$ % η_{total}
- space-charge considered
- no returned electrons
- max. wall loading
 435 W/cm^2

- By using compensation coils, the MDC concept may work.
- However, secondary electrons will reduce η a lot.

the alternative approach is very promising to handle secondary electrons



Concepts of MDCs for Gyrotrons


both \vec{A} and φ are
rotationally
symmetric

- Trajectories overlap each other, referred to Busch's theorem
- Can be modelled by the effective potential
- Weak magnetic field
- S.E. affect η enormous

at least one of the
potentials is
asymmetric


- Trajectories fully separable using the $\mathbf{E} \times \mathbf{B}$ drift
- Can be easily analyzed
- Proper magnetic field
- η is robust to S.E.

MDC based on $E \times B$ Drift



Transform the Electron Beam


hollow electron beam
at the entrance




source: Dohler, Int. J.
Electronics, 1983



thin electron beam
for the collection



Transform the Electron Beam



2D Projection of Transversal Magnetic Field



- Flux coordinates α and β for $\mathbf{B} = \nabla\alpha \times \nabla\beta$ (D'haeseleer; Flux Coordinates and Magnetic Field Structure; *Springer*)
 - Points with either α or β constant are on a magnetic field surface
 - Points with both α and β constant are on a magnetic field line
- For a 2D plane with infinitely long current \mathbf{J} perpendicular to the plane:

$$\nabla^2 \alpha = -J$$


- Has a simple Green's function solution.

2D Projection of Transversal Magnetic Field


- Symmetric currents perpendicular to xy-plane in four quadrants
- Hollow electron beam are transformed to very thin sheet beams
- A little complicated, but this is only a **conceptual proof design**



3D View of Coils and the Magnetic Field





3D Perspective Cut View of the Geometry



Electrodes and Voltages

- Five stages
- Depression voltages are based on the optimal voltages for a zero-thickness beam
- Maximal field strength is far below breakdown



Simulation Example

- A 5-stage collector with $\eta = 86 - 88 \%$
- Secondary electrons will be taken into account later



Secondary Electrons

- Shapes of electrodes are adjusted for secondary electrons
- Even with copper (high SEY material), η is reduced from 86 % to 82 %
- Has to be further investigated to minimize the affect




Conclusion

- Concepts are compared
 - Rotationally symmetric MDCs are intuitive, but S. E. reduce η enormous
 - Asymmetric $\mathbf{E} \times \mathbf{B}$ MDC can work robustly with S. E.
- $\mathbf{E} \times \mathbf{B}$ MDC requires thin beam → transform hollow beam to sheet beam
- **Conceptual validation** of the electron beam transform and $\mathbf{E} \times \mathbf{B}$ MDC using CST
 - Gyrotron magnet, plus several realistic normal-conducting trim coils
 - Realistic spent electron beam
 - Secondary electrons
- Preliminary simulation of a 5-stage collector
 - $\eta_{\text{col}} = 86 \%$ w/o secondary electrons
 - $\eta_{\text{col}} = 82 \%$ for copper, with secondary electrons ($\eta_{\text{total}} > 67 \%$)
- Alternative types $\mathbf{E} \times \mathbf{B}$ collectors are under investigation

Backup Slides

Create a Homogeneous Magnetic Field

- Create a field homogeneous field ($B = 35.6 \text{ mT}$) in the collector region using additional coils regarding the stray field of gyrotron main magnet
- Electron beam at the collector entrance has the radius of $131 \pm 4 \text{ mm}$ (Compromise between collector size and amplitude of drift velocity)





2D Projection of Transversal Magnetic Field 1

Starting from a long **quadrupole**

- \times and \cdot stand for the sign of current
- Inter-connected by dashed lines

Basic considerations



- Quadrants-mirrored
- Diagonally symmetric



Heat Loading

Very low heat loading because

- Multiple stages already recuperates the most (88 %) energy.
- Heat is loaded on the total long structure along z .



Energy of Imported Spent Electron Beam

